

EICHER TERRA 25

TECHNICAL SPECIFICATIONS

Model	EICHER TERRA 25 HDr
Wheelbase	4000 mm
GVW	25,000 kgs
Ground Clearance	252 mm
Max speed	78 km/h
Engine	Cummins B5.9 BS3
Max Power	136.75 kW (183.3 HP) @2500 rpm

Max Torque	685 Nm (69.8 kgM) @1400 rpm
Clutch	380 mm dia. Single plate dry push type, with Clutch Booster
Gearbox	6 speed synchromesh gear box of 80KgM capacity
Steering	Hydraulic Power Assisted, Re-circulating Ball & Nut Type
Brakes	Service Brake: Dual Circuit, Full air, 'S' cam
	Parking Brake: Spring brakes acting at rear wheels LH/RH actuated
	Exhaust Brake available
Suspension	Semi-elliptical laminated leaf springs, Hydraulic double acting telescopic shock absorbers in front only
Frame	'C' Channel ladder type- 285x76x7mm with 6 mm full length stiffener
Wheels & Tyres	10.00 x 20 - 16 PR
Cabin	Ergonomically designed sleeper cabin, spacious, comfortable, safe and tilt-able cabin with molded roof liner.
Fuel Tank	220 Litres
Body Capacity	14 Cu.m
Overall Length (FBT)	7590 mm
Available options	Fully Built vehicle with 14 Cu.m box type body
	<u>Applications</u>

- Blue Metal
 - Coal
 - Cruiser Outbound
 - Sand
- Stones

Note: If the machine of the model shown is not available at the time of booking, it will be replaced with another brand model of machine like "TATA" "HINO" "ISUZU" etc. specifications of the machine are subject to change by the manufacturer without any prior notice. www.mononbd.com is not liable for any kinds of technical change.

VE.

EICHER

ĩ

